

# BLISS ALBIS




## Albis Collection

### DESIGN

Repeat (Weft x Warp direction):	---	---
Roll lenght:	30 m	(32 yards)
Application:	Upholstery & not tensioned upholstery	

### PROPERTIES



Composition:	100% Solution Dyed Acrylic		
Width:	300 cm	(55")	
Weight:	140 g/m <sup>2</sup>	(4,13 oz/yd <sup>2</sup> )	UNE 40339
Resistance to surface wetting - Spray Test:	100	note (max. 100)	UNE-EN ISO 4920
Warp/Weft tensile strength:	75/85	daN/5 cm	UNE-EN ISO 13934-1
Warp/Weft tear resistance:	15/20	daN	UNE-EN ISO 13937-2
Warp/Weft dimensional change in washing:	<2/<1	%	UNE-EN ISO 5077
Colour fastness to artifical weathering:	≥ 7	note blue scale (max. 8)	UNE-EN ISO 105-B04
Colour fastness to artifical light:	≥ 7	note blue scale (max. 8)	UNE-EN ISO 105-B02
Colour fastness to chlorinated water (from pools):	5	note (max. 5)	UNE-EN ISO 105-E03
Colour fastness to seawater:	5	note (max. 5)	UNE-EN ISO 105-E02

Tolerance +/- 5% average values. Non-contractual information. The data are result of tests performed in our laboratories.  
For more technical information, please contact us at [info@blisscitel.com](mailto:info@blisscitel.com).

### FIRE BEHAVIOR CERTIFICATES

Class 1 (NFPA 260) · Pass (CA TB 117)  
Pass (BS 5852 -1) · Pass (EN 1021-1)

### CARE&CLEAN



Washing instructions:

Remove dust with a vacuum cleaner, without rubbing. Clean with a sponge or a soft brush dampened with water and soap.  
Ironing re-activates treatment

### WARRANTY

5 years  
Made in Europe