

BLISS BORAS

ESCANIA COLLECTION


DESIGN

Repeat (Weft x Warp direction): 2,3 cm x 1,4 cm 0,91 in. x 0,55 in.

Roll lenght: 50 m (55 yards)

Application: Upholstery & not tensioned upholstery

PROPERTIES



Composition: 100% Solution Dyed Acrylic

Width: 140 cm (55")

Weight: 360 g/m² (10,62 oz/yd²) UNE 40339

Resistance to surface wetting - Spray Test: 100 note (max. 100) UNE-EN ISO 4920

Oil Repellency ≥5 AATCC 118

Warp/Weft tensile strength: 245/155 daN/5 cm UNE-EN ISO 13934-1

Warp/Weft tear resistance: 14/16 daN UNE-EN ISO 13937-2

Warp/Weft seam strength: 30/30 daN UNE-EN ISO 13935-1

Warp/Weft dimensional change in washing: <1/<0,5 % UNE-EN ISO 5077

Fabric propensity to surface pilling : 5 note (max. 5) UNE EN ISO 12945-2

Colour fastness to artificial weathering: ≥ 7 note blue scale (max. 8) UNE-EN ISO 105-B04

Colour fastness to artificial light: ≥ 7 note blue scale (max. 8) UNE-EN ISO 105-B02

Colour fastness to chlorinated water (from pools): 5 note (max. 5) UNE-EN ISO 105-E03

Colour fastness to seawater: 5 note (max. 5) UNE-EN ISO 105-E02

Tolerance +/- 5% average values. Non-contractual information. The data are result of tests performed in our laboratories.

For more technical information, please contact us at info@blisscitel.com.

FIRE BEHAVIOR CERTIFICATES

Class 1 (NFPA 260) · Pass (CA TB 117)

Pass (BS 5852 -1) · Pass (EN 1021-1)

CARE&CLEAN



Washing instructions:



Remove dust with a vacuum cleaner, without rubbing. Clean with a sponge or a soft brush dampened with water and soap.

Ironing re-activates treatment

WARRANTY

5 years

Made in Europe