

BLISS PANAMA




Panama Collection

DESIGN

Repeat (Weft x Warp direction):	---	---
Roll lenght:	50 m	(55 yards)
Application:	Upholstery & not tensioned upholstery	

PROPERTIES



Composition:	100% Solution Dyed Acrylic	
Width:	140 cm	(55")
Weight:	235 g/m ²	(6,9325 oz/yd ² UNE 40339)
Resistance to surface wetting - Spray Test:	100 note (max. 100)	UNE-EN ISO 4920
Warp/Weft tensile strength:	160/100 daN/5 cm	UNE-EN ISO 13934-1
Warp/Weft tear resistance:	25/20 daN	UNE-EN ISO 13937-2
Warp/Weft seam strength:	25/25 daN	UNE-EN ISO 13935-1
Warp/Weft dimensional change in washing:	≤1 / ≤0,5 %	UNE-EN ISO 5077
Fabric propensity to surface pilling :	4 note (max. 5)	UNE EN ISO 12945-2
Colour fastness to artifical weathering:	≥ 7 note blue scale (max. 8)	UNE-EN ISO 105-B04
Colour fastness to artifical light:	≥ 7 note blue scale (max. 8)	UNE-EN ISO 105-B02
Colour fastness to chlorinated water (from pools):	5 note (max. 5)	UNE-EN ISO 105-E03
Colour fastness to seawater:	5 note (max. 5)	UNE-EN ISO 105-E02

Tolerance +/- 5% average values. Non-contractual information. The data are result of tests performed in our laboratories.

For more technical information, please contact us at info@blisscitel.com.

FIRE BEHAVIOR CERTIFICATES

Class 1 (NFPA 260) · Pass (CA TB 117)

Pass (BS 5852 -1) · Pass (EN 1021-1)

CARE&CLEAN



Washing instructions:



Remove dust with a vacuum cleaner, without rubbing. Clean with a sponge or a soft brush dampened with water and soap.

Ironing re-activates treatment

WARRANTY

5 years

Made in Europe