


# BLISS RIGA

## ESCANIA COLLECTION

### DESIGN

|                                 |                                       |                         |
|---------------------------------|---------------------------------------|-------------------------|
| Repeat (Weft x Warp direction): | 2,5 cm (Top - Bottom)                 | 0,98 in. (Top - Bottom) |
| Roll lenght:                    | 50 m                                  | (55 yards)              |
| Application:                    | Upholstery & not tensioned upholstery |                         |

### PROPERTIES



|                                                    |                              |                                       |
|----------------------------------------------------|------------------------------|---------------------------------------|
| Composition:                                       | 100% Solution Dyed Acrylic   |                                       |
| Width:                                             | 140 cm                       | (55")                                 |
| Weight:                                            | 285 g/m <sup>2</sup>         | (8,4075 oz/yd <sup>2</sup> UNE 40339) |
| Resistance to surface wetting - Spray Test:        | 100 note (max. 100)          | UNE-EN ISO 4920                       |
| Oil Repellency                                     | ≥5                           | AATCC 118                             |
| Warp/Weft tensile strength:                        | 240/80 daN/5 cm              | UNE-EN ISO 13934-1                    |
| Warp/Weft tear resistance:                         | 22/15 daN                    | UNE-EN ISO 13937-2                    |
| Warp/Weft seam strength:                           | 25/25 daN                    | UNE-EN ISO 13935-1                    |
| Warp/Weft dimensional change in washing:           | <0,5/<0,5 %                  | UNE-EN ISO 5077                       |
| Fabric propensity to surface pilling :             | 5 note (max. 5)              | UNE EN ISO 12945-2                    |
| Colour fastness to artifical weathering:           | ≥ 7 note blue scale (max. 8) | UNE-EN ISO 105-B04                    |
| Colour fastness to artifical light:                | ≥ 7 note blue scale (max. 8) | UNE-EN ISO 105-B02                    |
| Colour fastness to chlorinated water (from pools): | 5 note (max. 5)              | UNE-EN ISO 105-E03                    |
| Colour fastness to seawater:                       | 5 note (max. 5)              | UNE-EN ISO 105-E02                    |

Tolerance +/- 5% average values. Non-contractual information. The data are result of tests performed in our laboratories.

For more technical information, please contact us at [info@blisscitel.com](mailto:info@blisscitel.com).

### FIRE BEHAVIOR CERTIFICATES

Class 1 (NFPA 260) · Pass (CA TB 117)

Pass (BS 5852 -1) · Pass (EN 1021-1)

### CARE&CLEAN



#### Washing instructions:



Remove dust with a vacuum cleaner, without rubbing. Clean with a sponge or a soft brush dampened with water and soap.

Ironing re-activates treatment

### WARRANTY

5 years

Made in Europe