

BLISS ROTTERDAM

URBAN COLLECTION

DESIGN

Repeat (Weft x Warp direction):

Roll length:


50 m

(55 yards)

Application:

Upholstery & not tensioned upholstery

PROPERTIES



Composition:

100% Solution Dyed Acrylic

Width:

140 cm

(55")

Weight:

260 g/m²

(7,67 oz/yd²)

UNE 40339

Resistance to surface wetting - Spray Test:

100 note (max. 100)

UNE-EN ISO 4920

Oil Repellency

≥5

AATCC 118

Warp/Weft tensile strength:

160/125 daN/5 cm

UNE-EN ISO 13934-1

Warp/Weft tear resistance:

10/22 daN

UNE-EN ISO 13937-2

Warp/Weft seam strength:

26/30 daN

UNE-EN ISO 13935-1

Warp/Weft dimensional change in washing:

<1/<0,5 %

UNE-EN ISO 5077

Fabric propensity to surface pilling :

5 note (max. 5)

UNE EN ISO 12945-2

Colour fastness to artificial weathering:

≥ 7 note blue scale (max. 8)

UNE-EN ISO 105-B04

Colour fastness to artificial light:

≥ 7 note blue scale (max. 8)

UNE-EN ISO 105-B02

Colour fastness to chlorinated water (from pools):

5 note (max. 5)

UNE-EN ISO 105-E03

Colour fastness to seawater:

5 note (max. 5)

UNE-EN ISO 105-E02

Tolerance +/- 5% average values. Non-contractual information. The data are result of tests performed in our laboratories.

For more technical information, please contact us at info@blisscitel.com.

FIRE BEHAVIOR CERTIFICATES

Class 1 (NFPA 260) · Pass (CA TB 117)

Pass (BS 5852 -1) · Pass (EN 1021-1)

CARE&CLEAN



Washing instructions:



Remove dust with a vacuum cleaner, without rubbing. Clean with a sponge or a soft brush dampened with water and soap.

Ironing re-activates treatment

WARRANTY

5 years

Made in Europe