

## BLISS SPROUT




### Roots Collection

#### DESIGN

|                                 |                                       |                     |
|---------------------------------|---------------------------------------|---------------------|
| Repeat (Weft x Warp direction): | 23 cm x 21 cm                         | 9,05 in. x 8,27 in. |
| Roll lenght:                    | 50 m                                  | (55 yards)          |
| Application:                    | Upholstery & not tensioned upholstery |                     |

#### PROPERTIES



|                                                    |                              |                            |                    |
|----------------------------------------------------|------------------------------|----------------------------|--------------------|
| Composition:                                       | 100% Solution Dyed Acrylic   |                            |                    |
| Width:                                             | 140 cm                       | (55")                      |                    |
| Weight:                                            | 240 g/m <sup>2</sup>         | (7,08 oz/yd <sup>2</sup> ) | UNE 40339          |
| Resistance to surface wetting - Spray Test:        | 100 note (max. 100)          |                            | UNE-EN ISO 4920    |
| Warp/Weft tensile strength:                        | 155/110 daN/5 cm             |                            | UNE-EN ISO 13934-1 |
| Warp/Weft tear resistance:                         | 13/16 daN                    |                            | UNE-EN ISO 13937-2 |
| Warp/Weft seam strength:                           | 25/25 daN                    |                            | UNE-EN ISO 13935-1 |
| Warp/Weft dimensional change in washing:           | ≤1 / ≤0,5 %                  |                            | UNE-EN ISO 5077    |
| Fabric propensity to surface pilling :             | 5 note (max. 5)              |                            | UNE EN ISO 12945-2 |
| Colour fastness to artifical weathering:           | ≥ 7 note blue scale (max. 8) |                            | UNE-EN ISO 105-B04 |
| Colour fastness to artifical light:                | ≥ 7 note blue scale (max. 8) |                            | UNE-EN ISO 105-B02 |
| Colour fastness to chlorinated water (from pools): | 5 note (max. 5)              |                            | UNE-EN ISO 105-E03 |
| Colour fastness to seawater:                       | 5 note (max. 5)              |                            | UNE-EN ISO 105-E02 |

Tolerance +/- 5% average values. Non-contractual information. The data are result of tests performed in our laboratories.

For more technical information, please contact us at [info@blisscitel.com](mailto:info@blisscitel.com).

#### FIRE BEHAVIOR CERTIFICATES

Class 1 (NFPA 260) · Pass (CA TB 117)

Pass (BS 5852 -1) · Pass (EN 1021-1)

#### CARE&CLEAN



#### Washing instructions:



Remove dust with a vacuum cleaner, without rubbing. Clean with a sponge or a soft brush dampened with water and soap.

Ironing re-activates treatment

#### WARRANTY

5 years

Made in Europe