

BLISS TUSSET




Born Collection

DESIGN

Repeat (Weft x Warp direction):	1 cm x 1 cm	0,39 in. X 0,39 in.
Roll lenght:	50 m	(55 yards)
Application:	Upholstery & not tensioned upholstery	

PROPERTIES



Composition:	100% Solution Dyed Acrylic		
Width:	140 cm	(55")	
Weight:	400 g/m ²	(11,8 oz/yd ²)	UNE 40339
Resistance to surface wetting - Spray Test:	100 note (max. 100)		UNE-EN ISO 4920
Warp/Weft tensile strength:	240/200 daN/5 cm		UNE-EN ISO 13934-1
Warp/Weft tear resistance:	60/65 daN		UNE-EN ISO 13937-2
Warp/Weft seam strength:	25/25 daN		UNE-EN ISO 13935-1
Warp/Weft dimensional change in washing:	≤1,5 / ≤0,5 %		UNE-EN ISO 5077
Fabric propensity to surface pilling :	5 note (max. 5)		UNE EN ISO 12945-2
Colour fastness to artifical weathering:	≥ 7 note blue scale (max. 8)		UNE-EN ISO 105-B04
Colour fastness to artifical light:	≥ 7 note blue scale (max. 8)		UNE-EN ISO 105-B02
Colour fastness to chlorinated water (from pools):	5 note (max. 5)		UNE-EN ISO 105-E03
Colour fastness to seawater:	5 note (max. 5)		UNE-EN ISO 105-E02

Tolerance +/- 5% average values. Non-contractual information. The data are result of tests performed in our laboratories.

For more technical information, please contact us at info@blisscitel.com.

FIRE BEHAVIOR CERTIFICATES

Class 1 (NFPA 260) · Pass (CA TB 117)
Pass (BS 5852 -1) · Pass (EN 1021-1)

CARE&CLEAN



Washing instructions:



Remove dust with a vacuum cleaner, without rubbing. Clean with a sponge or a soft brush dampened with water and soap.

Ironing re-activates treatment

WARRANTY

5 years

Made in Europe