



# DOCRIL

OEKO  
TEX®

## SOLAR PROTECTION

Roll lenght: 60 m (65 yards)

Application: Awning, Umbrella, Sunshade

## PROPERTIES



Composition: 100% Solution Dyed Acrylic

Width: 120 cm (47") 153 cm (60")

Weight: 295 g/m<sup>2</sup> (8,70 oz/yd<sup>2</sup>) UNE 40339

Water penetration resistance: 35 cm H<sub>2</sub>O (≥ 13,8" H<sub>2</sub>O) UNE EN ISO 811

Resistance to surface wetting - Spray Test: 100 note (max. 100) UNE-EN ISO 4920

Oil Repellency: ≥ 5 AATCC 118

Warp/Weft tensile strength: 130/75 daN/5 cm (292/167 lbf/2 in.) UNE-EN ISO 13934-1

Warp/Weft elongation at break: ≤ 25/≤ 20 % UNE-EN ISO 13934-1

Warp/Weft tear strength: 5/3 daN (11,3/6,8 lbf/2 in.) UNE-EN ISO 13937-2

Colour fastness to artifical light: ≥ 7 note blue scale (max. 8) UNE-EN ISO 105-B02

Colour fastness to artifical weathering: ≥ 7 note blue scale (max. 8) UNE-EN ISO 105-B04

Colour fastness to seawater: 5 note (max. 5) UNE-EN ISO 105-E02

Colour fastness to chlorinated water (from pools): 5 note (max. 5) UNE-EN ISO 105-E03

Tolerance +/- 5% average values. Non-contractual information. The data are result of tests performed in our laboratories.

For more technical information, please contact us at [info@citel.com](mailto:info@citel.com)

## CARE&CLEAN



Maintenance instructions: Remove dust with a vacuum cleaner, without rubbing. Clean with a sponge or a soft brush dampened with water and soap.

When used in awnings, it is very important to allow the fabric to dry completely before roll it up

## WARRANTY

10 years

Made in Europe