

MIXTRIM




Mixtrim Collection

DESIGN

Roll lenght: 30 m (32,8 yards)

Application: Upholstery & not tensioned upholstery

PROPERTIES



Composition: 37/67% Solution Dyed Acrylic/Poliester +PVC

Width: 300 cm (55")

Weight: 340 g/m² (12 oz/yd²) UNE 40339

Resistance to surface wetting - Spray Test: 100 note (max. 100) UNE-EN ISO 4920

Warp/Weft tensile strength: 145/120 daN/5 cm UNE-EN ISO 13934-1

Warp/Weft tear resistance: 12/10 daN UNE-EN ISO 13937-2

Abrasion resistance by the Martindale Method (*): 100.000 cycles UNE EN ISO 12947-2

Colour fastness to artifical weathering: ≥ 7 note blue scale (max. 8) UNE-EN ISO 105-B04

Colour fastness to artifical light: ≥ 7 note blue scale (max. 8) UNE-EN ISO 105-B02

Colour fastness to chlorinated water (from pools): 5 note (max. 5) UNE-EN ISO 105-E03

Colour fastness to seawater: 5 note (max. 5) UNE-EN ISO 105-E02

Tolerance +/- 5% average values. Non-contractual information. The data are result of tests performed in our laboratories.

(*) The results of this test may vary depending on the laboratory where the test was performed

For more technical information, please contact us at info@blisscitel.com.

FIRE BEHAVIOR CERTIFICATES

Class 1 (NFPA 260) · Pass (CA TB 117)

Pass (BS 5852 -1) · Pass (EN 1021-1)

CARE&CLEAN



Washing instructions:



Remove dust with a vacuum cleaner, without rubbing. Clean with a sponge or a soft brush dampened with water and soap.

Ironing re-activates treatment

WARRANTY

3 years

Made in Europe